

## Cetol® DEK

Cetol DEK is a translucent satin topcoat developed for use in the Cetol DEK system. It was developed using a special alkyd resin and selected ultraviolet absorbing pigments. As a topcoat Cetol DEK enhances the natural beauty of wood while providing excellent protection.

Highly transparent; ensures optimum visibility of the wood grain, enhancing the appearance of the wood.

Withstands physical wear.

Microporous; allows the wood to breathe.

Weather resistant.

Water repellent.

Very easy application.

Used as a topcoat over Cetol DEK Base.

**Method** - Good quality long-haired, natural bristle brush. Black China brush recommended.

**Temperature** - 10° C - 35° C (50° F - 95° F)

**Thinning** - None; ready to use after stirring thoroughly.

**Cleaning of Equipment** - Mineral spirits.

**Coverage** - Approximately 7.5-10 sq. m. per liter (300-400 sq. ft. per U.S. gallon) per coat on smooth wood.

**Drying Time** - Touch dry after 3-4 hours, recoatable after 24 hours at 20° C (68° F) and 65% relative humidity.

During application, moisture content of wood substrate should not exceed 18%.

## CHARACTERISTICS

## USE

## APPLICATION

## GENERAL REMARKS

**Viscosity** - 39-44 Ford Cup #4 at 23° C (73.4° F)

**Density** - 0.89-0.90 kg/dm<sup>3</sup>

**Solids by Weight** - 40.9 - 41.6%

**Solids by Volume** - 34.20 - 34.61%

**Gloss Level** - Satin Finish

**Flow** - Very Good

**Durability** - Good

**V.O.C.** - Less than 4.59 lbs./gal., 550 g/L - water free

(005) Natural Oak

(077) Cedar

(078) Natural

U.S. gallon, U.S. 5 gallon

**Shelf Life** - Approximately 5 years in an unopened container.

**FLASHPOINT:**

Approx. 40.5° C (105° F) (DIN 53213)

**WARNINGS:**

DANGER! RAGS, STEEL WOOL, BRUSHES, ROLLERS AND ANY WASTE WET, SOAKED WITH THIS PRODUCT MAY SPONTANEOUSLY CATCH FIRE IF IMPROPERLY DISPOSED OR STORED. To avoid a spontaneous combustion fire, immediately after each use place rags, steel wool, brushes, rollers or waste in a sealed, water-filled metal container. Keep away from combustible materials. For disposal guidance, contact your household refuse collection service, fire department, county or state government environmental control agency. Harmful or fatal if swallowed. Keep out of reach of children. Keep away from open flame or spark. Use only with adequate ventilation

**FIRST AID TREATMENT:**

Refer to the Material Safety Data Sheet.

The technical information and suggestions for use made herein are based on Akzo Nobel Coatings Inc.'s research and experience and are believed to be reliable, but such information and suggestions do not constitute a warranty.

Since Akzo Nobel Coatings Inc. has no control over the conditions under which the product is transported, stored, handled, used or applied, buyers must determine for themselves, by preliminary tests or otherwise, the suitability of the product for their purposes. When testing, the complete system that has been chosen must be applied.

## PROPERTIES

## COLOR RANGE

## PACKAGING

## STORAGE

## HEALTH & SAFETY DATA

## PRODUCT DISCLAIMER