

M A T E R I A L S A F E T Y D A T A S H E E T

SECTION I - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME : ORIGINAL SATIN FINISH
IDENTIFICATION NUMBER: TB 6022 **DATE PRINTED:** 08/15/02
PRODUCT USE/CLASS : Architectural/Wood Finish

SUPPLIER: Waterlox Coatings Corporation 9808 Meech Avenue Cleveland, OH 44105 E-mail: info@waterlox.com	MANUFACTURER: Waterlox Coatings Corporation 9808 Meech Avenue Cleveland, OH 44105 E-mail: info@waterlox.com
--	--

EMERGENCY TELEPHONE: 800.321.0377 8:00am to 4:30pm M-F	EMERGENCY TELEPHONE: 800.321.0377 8:00am to 4:30pm M-F
--	--

PREPARER: Chris Harding, **PHONE:** 216.641.4877, **PREPARE DATE:** 08/15/02

SECTION II - COMPOSITION/INFORMATION ON INGREDIENTS

CHEMICAL NAME	CAS NUMBER	WT. PERCENT IS LESS THAN	OCCUPATIONAL EXPOSURE LIMITS
		TLV-TWA	TLV-STEL PEL-TWA PEL-CEILING SKIN

STODDARD SOLVENT	8052-41-3	70.0 %	100 PPM	NO
1, 3, 5-TRIMETHYLBENZENE	108-67-8	5.0 %	25 PPM	NO
1, 2, 4-TRIMETHYLBENZENE	95-63-6	5.0 %	25 PPM	NO
COBALT NAPHTHENATE	61789-51-3	1.0 %	0.1mg/m3	NO

(See Section 11 for abbreviation legend)

SECTION III - PHYSICAL DATA

BOILING RANGE : 300 - 390 F ODOR : Hydrocarbon APPEARANCE : Milky amber SOLUBILITY IN H2O : Insoluble VOLATILE BY WEIGHT: 71.9% VOCS, lbs/gal : 5.01	VAPOR DENSITY : Is heavier than air SPECIFIC GRAVITY: 0.8366 EVAPORATION RATE: Is slower than Ether VOLATILE BY VOL.: 76.1% VOCS, grams/ltr : 600
---	--

OTHER DATA: No Information.

(See Section XI for abbreviation legend)

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 104 F (TAGLIABUE CLOSED CUP)	LOWER EXPLOSIVE LIMIT: 0.8 % UPPER EXPLOSIVE LIMIT: 6.0 %
---	--

(Continued on Page 2)

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

EXTINGUISHING MEDIA: ALCOHOL FOAM CO2 DRY CHEMICAL FOAM

UNUSUAL FIRE AND EXPLOSION HAZARDS: VAPORS ARE HEAVIER THAN AIR AND MAY ACCUMULATE IN LOW AREAS OR AREAS INADEQUATELY VENTILATED. VAPORS MAY ALSO TRAVEL ALONG THE GROUND TO BE IGNITED AT LOCATIONS DISTANT FROM THE HANDLING SITE. WARNING! FLAMMABLE. ELIMINATE ALL IGNITION SOURCES. HANDLING EQUIPMENT MUST BE GROUNDED TO PREVENT SPARKING.

SPECIAL FIREFIGHTING PROCEDURES: EVACUATE HAZARD AREA OF UNPROTECTED PERSONNEL. WEAR PROPER PROTECTIVE CLOTHING INCLUDING A NIOSH APPROVED SELF-CONTAINED BREATHING APPARATUS. COOL FIRE-EXPOSED CONTAINERS WITH WATER.

SECTION V - HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE - EYE CONTACT: CAUSES EYE IRRITATION

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: PROLONGED AND REPEATED LIQUID CONTACT CAN CAUSE DEFATTING AND DRYING OF THE SKIN WHICH MAY RESULT IN SKIN IRRITATION AND DERMATITIS.

EFFECTS OF OVEREXPOSURE - INHALATION: OVEREXPOSURE CAN LEAD TO CENTRAL NERVOUS SYSTEM DEPRESSION PRODUCING SUCH EFFECTS AS HEADACHE, DIZZINESS, NAUSEA, AND LOSS OF CONSCIOUSNESS.

EFFECTS OF OVEREXPOSURE - INGESTION: IRRITATING TO MOUTH, THROAT AND STOMACH.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: No Information.

FIRST AID - EYE CONTACT: IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER WHILE HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION IF IRRITATION PERSISTS FOR MORE THAN A FEW MINUTES.

FIRST AID - SKIN CONTACT: WASH WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING AND SHOES; DO NOT REUSE UNTIL CLEANED. IF PERSISTENT IRRITATION OCCURS, GET MEDICAL ATTENTION.

FIRST AID - INHALATION: REMOVE VICTIM TO FRESH AIR AND PROVIDE OXYGEN IF BREATHING IS DIFFICULT. GIVE ARTIFICIAL RESPIRATION IF NOT BREATHING. GET MEDICAL ATTENTION.

FIRST AID - INGESTION: IF SWALLOWED, DO NOT INDUCE VOMITING!! GET IMMEDIATE MEDICAL ATTENTION.

PRIMARY ROUTE(S) OF ENTRY: INHALATION INGESTION

(Continued on Page 3)

SECTION VI - REACTIVITY DATA

HAZARDOUS DECOMPOSITION PRODUCTS: CARBON MONOXIDE AND UNIDENTIFIED ORGANIC COMPOUNDS MAY BE FORMED DURING COMBUSTION.

CONDITIONS TO AVOID: AVOID HEAT, SPARKS, AND OPEN FLAME.

INCOMPATIBILITY: AVOID CONTACT WITH STRONG OXIDIZING AGENTS.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR UNDER NORMAL CONDITIONS.

STABILITY: THIS PRODUCT IS STABLE UNDER NORMAL STORAGE CONDITIONS.

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: LARGE SPILLS: EVACUATE THE HAZARD AREA OF UNPROTECTED PERSONNEL. WEAR APPROPRIATE RESPIRATOR AND PROTECTIVE CLOTHING. DIKE AND CONTAIN.

WASTE DISPOSAL METHOD: PLACE CONTAMINATED MATERIAL IN SUITABLE CONTAINERS FOR DISPOSAL.

SECTION VIII - SAFE HANDLING AND USE INFORMATION

RESPIRATORY PROTECTION: IF YOU ARE WORKING IN CONFINED SPACES AND/OR EXPOSURE MAY OR DOES EXCEED OCCUPATIONAL EXPOSURE LIMITS (SECTION II) USE A NIOSH - APPROVED RESPIRATOR TO PREVENT OVEREXPOSURE.

VENTILATION: USE VENTILATION ADEQUATE TO KEEP EXPOSURES (AIRBORNE LEVELS, DUST, FUME, VAPOR, ETC) BELOW RECOMMENDED EXPOSURE LIMITS.

SKIN PROTECTION: RECOMMENDED FOR PROLONGED OR REPEATED CONTACT.

EYE PROTECTION: WEAR GOGGLES TO PREVENT EYE CONTACT

OTHER PROTECTIVE EQUIPMENT: WEAR PROTECTIVE CLOTHING AS REQUIRED TO PREVENT SKIN CONTACT.

HYGIENIC PRACTICES: WASH THOROUGHLY AFTER HANDLING. WASH WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING OR USING TOILET FACILITIES. LAUNDRY CONTAMINATED CLOTHING BEFORE REUSE.

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: MAINTAIN ADEQUATE VENTILATION WHEN PRODUCT IS IN USE. KEEP CONTAINERS TIGHTLY CLOSED IN STORAGE.

OTHER PRECAUTIONS: DO NOT WELD, HEAT OR DRILL ON OR NEAR CONTAINER; EVEN EMPTIED CONTAINERS CAN CONTAIN EXPLOSIVE VAPORS. PROVIDE RESPIRATORY

(Continued on Page 4)

SECTION IX - SPECIAL PRECAUTIONS

PROTECTION AGAINST SMOKE AND FUMES GENERATED DURING BURNING OR DUSTS GENERATED DURING REMOVAL OF DRY COATINGS.

SECTION X - HMIS RATINGS

HMIS RATINGS - HEALTH: 2 FLAMMABILITY: 2 REACTIVITY: 0

SECTION XI - OTHER REGULATIONS

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

----- CHEMICAL NAME -----	CAS NUMBER	WT/WT % IS LESS THAN
1,3,5-TRIMETHYLBENZENE	108-67-8	5.0 %
1,2,4-TRIMETHYLBENZENE	95-63-6	5.0 %
COBALT NAPHTHENATE	61789-51-3	1.0 %

U.S. STATE REGULATIONS: AS FOLLOWS -

CALIFORNIA PROPOSITION 65:

WARNING: The chemical(s) noted below and contained in this product, are known to the state of California to cause cancer, birth defects or other reproductive harm:

----- CHEMICAL NAME ----- CAS NUMBER
No Proposition 65 chemicals exist in this product.

PREVIOUS MSDS REVISION DATE: 04/25/00

REASON FOR REVISION: New msds software

LEGEND: N.A. - Not Applicable, N.E. - Not Established,
N.D. - Not Determined

The information contained on this MSDS has been checked and should be accurate. However, it is the responsibility of the user to comply with all Federal, State, and Local laws and regulations.